




# S900

## Surface mounted rack & pinion door closer EN 2-6 power adjustable by spring

### Performance

- EN 2-6 adjustable power.  
(Fig.1 EN 2-6 / 1400mm maximum door width).  
(Fig.6 EN 3-5 / 1250mm maximum door width).
- CE marked (DOP-SHL-60).
- Certifire approved up to FD120 on timber doors. 
- Tested to BS EN 1154 - Fig.1 

4	8	6	2	1	1	3
---	---	---	---	---	---	---

  
- Fig.6 

4	8	5	3	1	1	3
---	---	---	---	---	---	---

### Specifications

- Rack & Pinion mechanism with matching flat form armset.
- Extruded body.
- Universal application (Fig.1, Fig.6 & Fig.61).
- Adjustable closing speed and independent latch action.
- Adjustable mechanical backcheck.
- Capable of meeting the opening force requirements of ADM and BS8300 (1050mm minimum door width at EN3).

### Models

**S900** - Universal mounting (Fig.1, Fig.6 & Fig.61).

Add suffix **.SR** for semi radius cover version.

Add suffix **.MEC** for slide plate option.


### Finishes

**PSC • SES • SSN • RAL • BRO**


(Page 48-51 for further details).

### Dimensions

Closer with semi-radius (.SR)



Closer with slide plate (.MEC)



### Features

Fig.1 mounting.	✓
Fig.6 / Fig.61 mounting.	✓
Closing power EN size (Fig.1/Fig.6).	2-6 / 3-5
Adjustable closing speed, latch action and backcheck.	✓
Minimum door width to meet ADM/BS8300 at EN3.	1050mm
Optional mechanical hold open arm - Page 52. (Not CE marked or suitable for fire door applications).	S900.SES. HOA
Optional drop plate / mount plate available - Page 52.	S900.DP / MP
Warranty.	10 years



2. RACK & PINION CLOSERS

S900 SR in SBM finish